

SILICONE RESIN COMPOSITION AND LOW-VOLTAGE FIRE-RESISTING CABLE USING IT

Publication number: JP2003100149 (A)

Publication date: 2003-04-04

Inventor(s): NAKAMURA SHOICHIRO

Applicant(s): FUJIKURA LTD

Classification:

- international: *C08K3/34; C08K3/40; C08L83/04; H01B3/00; H01B3/46; H01B7/295; C08K3/00; C08L83/00; H01B3/00; H01B3/46; H01B7/17; (IPC1-7): H01B3/46; C08K3/34; C08K3/40; C08L83/04; H01B3/00; H01B7/295*


- European:

Application number: JP20010287081 20010920

Priority number(s): JP20010287081 20010920

Abstract of **JP 2003100149 (A)**

PROBLEM TO BE SOLVED: To provide high fire resistance and to enhance electric insulation capability of a fire-resisting insulating layer, in a low-voltage fire-resisting cable with the fire-resisting insulating layer made of a silicone resin composition formed on a conductor. **SOLUTION:** A substance with mica fine powder added in a silicone resin in addition to glass frit containing alkaline metal having a softening start temperature of 500 deg.C or below and a crystallization start temperature of 840 deg.C or below is used for this silicone resin composition. This low-voltage fire-resisting cable with the fire-resisting insulating layer 2 made of the silicone resin composition and cross-linked formed on the conductor 1 is used.



Data supplied from the **esp@cenet** database — Worldwide